



POWERED BY INNOVATION

P20 Series Connected Coil Performance Specification

General and 6 Lead Motor Specifications		UNITS	Dash #	1	2	3	4	5	6
Force Constant	lb <sub>f</sub> /A			4.1	8.2	12.3	16.4	20.6	24.7
	N/A			18.3	36.6	54.9	73.1	91.4	109.7
Max Operating Temperature	°C			130	130	130	130	130	130
Maximum Temp. Rise	°C			105	105	105	105	105	105
Coil Resistance (6 lead @ 25°C)	Ω			5.82	11.64	17.46	23.28	29.10	34.92
Coil Resistance (6 lead @ Max. °C)	Ω			8.23	16.45	24.68	32.91	41.14	49.36
Inductance @ 1kHz	mH			1.8	3.6	5.4	7.2	9.0	10.8
Thermal Resistance (Bracket Top Mount)	°C/W			1.28	0.64	0.43	0.32	0.26	0.21
Continuous Power Top Mount (Max. °C)	W			82	164	246	327	409	491
Thermal Resistance, side mount (SP23, 1" hole spacing)	°C/W			1.80	0.90	0.60	0.45	0.36	0.30
Continuous Power using Side Mount (Max. °C)	W			58	117	175	233	292	350
Continuous Power, top mount to plate**(Max. °C)	W			43.5	70.6	95.0	118.6	141.8	164.7
Motor Constant	lb <sub>f</sub> /sqrt(W)			1.8	2.5	3.0	3.5	3.9	4.3
	N/sqrt(W)			7.81	11.04	13.52	15.62	17.46	19.13
Peak Power (Max. °C, 10% Duty)	W			819	1637	2456	3274	4093	4911
Back EMF Constant	V/inch/s			0.46	0.93	1.39	1.86	2.32	2.78
	V/m/s			18.3	36.6	54.9	73.1	91.4	109.7
Electrical Time Constant (@ 25°C)	ms			0.31	0.31	0.31	0.31	0.31	0.31
(@ 130°C)	ms			0.22	0.22	0.22	0.22	0.22	0.22
Maximum Line to Line Voltage	V <sub>rms</sub>			500	500	500	500	500	500
Coil Weight (HED adds 15g.[.033lb])	Pounds			0.4	0.9	1.3	1.7	2.1	2.6
	Kilograms			0.19	0.39	0.58	0.78	0.97	1.16
Coil length (inside magnet track without HED)	inch			2.41	4.81	7.21	9.61	12.01	14.41
HED increases coil length by 1.49 inch (37.8mm)	mm			61.2	122.2	183.1	244.1	305.1	366.0
Coil bracket length (without HED option)	inch			3.21	5.61	8.01	10.41	12.81	15.21
HED increases bracket length by 1.49inch, (37.8mm)	mm			81.5	142.5	203.5	264.4	325.4	386.3
Delta Connected Specifications		UNITS	Dash #	1	2	3	4	5	6
Force Constant	lb <sub>f</sub> /A			4.1	8.2	12.3	16.4	20.6	24.7
	N/A			18.3	36.6	54.9	73.1	91.4	109.7
Phase Resistance (Δ @ 25°C)	Ω			3.9	7.8	11.6	15.5	19.4	23.3
Phase Resistance (Δ @ Max. °C)	Ω			5.5	11.0	16.5	21.9	27.4	32.9
Inductance @ 1kHz	mH			1.2	2.4	3.6	4.8	6.0	7.2
Continuous Force	lb <sub>f</sub>			15.9	31.8	47.6	63.5	79.4	95.3
	N			70.6	141.3	211.9	282.6	353.2	423.9
Continuous Current	A			3.9	3.9	3.9	3.9	3.9	3.9
Peak Force*	lb <sub>f</sub>			50	100	151	201	251	301
	N			223	447	670	894	1117	1340
Peak Current*	A			12.2	12.2	12.2	12.2	12.2	12.2
Continuous Force, aluminum plate heat sink** (see below)	lb <sub>f</sub>			11.6	20.9	29.6	38.2	46.7	55.2
	N			51.5	92.8	131.8	170.1	207.9	245.5
Back EMF Constant	V/inch/s			0.5	0.9	1.4	1.9	2.3	2.8
	V/m/s			18.3	36.6	54.9	73.1	91.4	109.7
WYE connected Specifications		UNITS	Dash #	1	2	3	4	5	6
Force Constant	lb <sub>f</sub> /A			7.1	14.2	21.4	28.5	35.6	42.7
	N/A			31.7	63.3	95.0	126.7	158.4	190.0
Phase Resistance (Y @ 25°C)	Ω			11.6	23.3	34.9	46.6	58.2	69.8
Phase Resistance (Y @ Max. °C)	Ω			16.5	32.9	49.4	65.8	82.3	98.7
Inductance @ 1kHz	mH			3.6	7.2	10.8	14.4	18.1	21.7
Continuous Force	lb <sub>f</sub>			15.9	31.8	47.6	63.5	79.4	95.3
	N			70.6	141.3	211.9	282.6	353.2	423.9
Continuous Current	A			2.23	2.23	2.23	2.23	2.23	2.23
Peak Force*	lb <sub>f</sub>			50	100	151	201	251	301
	N			223	447	670	894	1117	1340
Peak Current*	A			7.05	7.05	7.05	7.05	7.05	7.05
Continuous Force, aluminum plate heat sink** (see below)	lb <sub>f</sub>			11.6	20.9	29.6	38.2	46.7	55.2
	N			51.5	92.8	131.8	170.1	207.9	245.5
Back EMF Constant	V/inch/s			0.8	1.6	2.4	3.2	4.0	4.8
	V/m/s			31.7	63.3	95.0	126.7	158.4	190.0

\* Notes:

Specifications based on heat sink maintained within 10°C of ambient temperature at motor bracket interface.  
 Dash 6 and larger coils may be constructed in multiple segments. Contact factory for availability.  
 On time of "Peak Power" (duration) less than 10 seconds.  
 Back EMF plus IR drop must not exceed "Maximum Terminal Voltage" listed.  
 Electrical cycle length is 2.4 inch (61mm).  
 Resistance Specifications do not include the cable resistance.  
 Custom cable required for peak current exceeding 17 ampere.  
 Cable adds 0.22Ω/m to 6-lead resistance, 0.146Ω/m to Delta resistance and 0.44Ω/m to WYE resistance.  
 \*\* Heat Sink is a 12" wide, 1/2" thick aluminum plate, extending 2" beyond each end of the coil bracket, in 258C free air.  
 Magnet Track weight is 13kg/m (9.0 pounds/foot).